



CANALKLER 250 S

Kanalspolslang speciellt utvecklad för professionell och säker kanal- och avloppsrengöring.

Egenskaper

- Extremt starkt yttergummi
- Hög flexibilitet, även vid låga temperaturer
- Deformationsbeständig
- Mycket hög draghållfasthet
- Textilarmerad
- Mycket lättarbetad
- Extra högt arbetstryck och säkerhet
- Låg friktion och lång livslängd

Teknisk beskrivning

- Innertub: SBR (svart, slät)
- Armering: Flätad aramid
- Yttergummi: SBR/NBR (svart, slätt)
- Temperaturområde: -30°C till +80°C

Övrig information

Samtliga fabriksopplade slangar är provtryckta med 375 bar och levereras med testcertifikat.



CANALKLER 250 S

Sewer jetting and heavy duty, high pressure water cleaning.

Advantages

- Very low sliding resistance
- Better flexibility, even at low temperatures
- Easy to handle and user friendly
- Deformation resistance
- Extra high strength and security due to aramide reinforcement
- Long service life

Technical description

- Inner tube: SBR (black, smooth)
- Reinforcement: aramide textile, braided
- Cover: SBR/NBR (black, smooth)
- Temperature range: -30°C to +80°C

Complementary information

All assembled hoses are pressure tested at 375 bar and have a unique hose number. Delivered with test certificate on each factory assembled hose.

CANALKLER 250 S



	5-3913040	5-3913060	5-3913080	5-3913100	5-3913120
	1/2"				
	13 mm (1/2")				
	25,6 mm				
	250 bar				
	-30°C – +80°C				
	0,4 kg/m				
	70 mm				
	40 m	60 m	80 m	100 m	120 m
	5-3919040	5-3919080	5-3919100	5-3919120	
	3/4"				
	19 mm (3/4")				
	31,6 mm				
	250 bar				
	-30°C – +80°C				
	0,6 kg/m				
	90 mm				
	40 m	80 m	100 m	120 m	
	5-3925040	5-3925050	5-3925080	5-3925100	
	1"				
	25 mm (1")				
	39,3 mm				
	250 bar				
	-30°C – +80°C				
	0,9 kg/m				
	100 mm				
	40 m	50 m	80 m	100 m	

	Anslutning Connection		Ytterdiameter Outer diameter		Temperaturområde Temperature working area		Böjningsradie Bending radius		Övrig information Other information
	Innerdiameter Inner diameter		Max arbetsstryck Max. working pressure		Vikt Weight		Leveranslängd Delivery length		

CANALKLER 250 S



	5-3925120	5-3925150	5-3925120-32	5-3925150-32
	1"	1"	1 1/4" *	1 1/4" *
	25 mm (1")			
	39,3 mm			
	250 bar			
	-30°C – +80°C			
	0,9 kg/m			
	100 mm			
	120 m	150 m	120 m	150 m
	-	-	*1 1/4" koppling /coupling	*1 1/4" koppling /coupling

	5-3925160	5-3925180	5-3925200	5-3925240
	1 1/4" *			
	25 mm (1")			
	39,3 mm			
	250 bar			
	-30°C – +80°C			
	0,9 kg/m			
	100 mm			
	160 m	180 m	200 m	240 m
	*1 1/4" koppling /coupling			

 Anslutning
Connection

 Innerdiameter
Inner diameter

 Ytterdiameter
Outer diameter

 Max arbetstryck
Max. working pressure

 Temperaturområde
Temperature working area

 Vikt
Weight

 Böjningsradie
Bending radius

 Leveranslängd
Delivery length

 Övrig information
Other information

CANALKLER 250 S



	5-3932040	5-3932080	5-3932120	5-3932150	5-3932160
	1¼"				
	32 mm (1¼")				
	47,6 mm				
	250 bar				
	-30°C – +80°C				
	1,1 kg/m				
	130 mm				
	40 m	80 m	120 m	150 m	160 m
	5-3932180	5-3932200			
	1¼"				
	32 mm (1¼")				
	47,6 mm				
	250 bar				
	-30°C – +80°C				
	1,1 kg/m				
	130 mm				
	180 m	200 m			
	5-3938120	5-3938150			
	1½"				
	38 mm (1½")				
	54 mm				
	250 bar				
	-30°C – +80°C				
	1,4 kg/m				
	155 mm				
	120 m	150 m			

 Anslutning
Connection

 Innerdiameter
Inner diameter

 Ytterdiameter
Outer diameter

 Max arbetsstryck
Max. working pressure

 Temperaturområde
Temperature working area

 Vikt
Weight

 Böjningsradie
Bending radius

 Leveranslängd
Delivery length

 Övrig information
Other information