



EXITFLEX

Högtrycksspolslang för professionellt användande.

Teknisk beskrivning

- Innertub: Polyamid
- Armering: Flätad, kopparlegerad stålarmoring
- Yttergummi: Polyuretan
- Temperaturområde: -40°C till +98°C



EXITFLEX

Hose for high pressure airless paint spray system. Suitable for applications requiring chemical resistance to solvents and aggressive fluids.

Technical description

- Inner tube: Polyamide
- Reinforcement: brass plated carbon steel
- Cover: Polyurethane
- Temperature range: -40°C to +98°C

EXITFLEX



	5-EF05-15	5-EF05-20	5-EF05-25	5-EF05-30	5-EF05-40	5-EF05-50
	1/8"					
	4,8 mm (3/16")					
	9,3 mm					
	350 bar					
	-40°C – +98°C					
	0,1 kg/m					
	35 mm					
	15 m	20 m	25 m	30 m	40 m	50 m
	5-EF06-20	5-EF06-25	5-EF06-30	5-EF06-50		
	1/4"					
	6,4 mm (1/4")					
	11,7 mm					
	325 bar					
	-40°C – +98°C					
	0,16 kg/m					
	45 mm					
	20 m	25 m	30 m	50 m		
	5-EF07-25	5-EF07-30	5-EF07-40	5-EF07-50		
	3/8"					
	9,6 mm (3/8")					
	15,2 mm					
	250 bar					
	-40°C – +98°C					
	0,23 kg/m					
	60 mm					
	25 m	30 m	40 m	50 m		

Anslutning
Connection

Ytterdiameter
Outer diameter

Temperaturområde
Temperature working area

Böjningsradie
Bending radius

Övrig information
Other information

Innerdiameter
Inner diameter

Max arbetstryck
Max. working pressure

Vikt
Weight

Leveranslängd
Delivery length