



## GOBLIN™

GOBLIN™ var föregångaren till BL Patent™. Båda har revolutionerat rengöringen av ledningar och används idag över hela världen. GOBLIN™ har förbättrats ytterligare, med inre väggar som dirigerar vattnet på ett sätt som säkerställer en vattenström med mindre turbulens. Genom denna konstruktion bibehåller vattnet sin energi. GOBLIN™ är dubbelt så effektiv som konventionella munstycken.

GOBLIN™ S har 4 utbytbara drivdysor och en frontdysa, vilken kan pluggas när så önskas. GOBLIN™ S är tillverkat i brons och används med släde.

GOBLIN™ L har 10 utbytbara drivdysor; fem med 30° vinkel och fem med 15°, som enkelt anpassas efter pumpkapacitet och slangdimension. GOBLIN™ L är även försedd med en frontdysa, vilken kan pluggas när så önskas. GOBLIN™ L är tillverkad i rostfritt stål och kan förses med slitkropp.



## GOBLIN™

GOBLIN™ was the predecessor to the Jaws®. They became revolutionary in the market and are widely used today all over the world. Since then we have improved the GOBLIN™ Sewer Nozzle. GOBLIN™ has water bearing walls to ensure smooth water streams with less turbulence. By this construction the water energy is kept until it becomes useful for cleaning the pipes. GOBLIN™ is about twice as effective as conventional nozzles with drilled interior.

GOBLIN™ S has 4 exchangeable thrusting jets and one front jet, which can be plugged when not used. GOBLIN™ S is made of bronze and is used with sled.


GOBLIN™ L has 10 exchangeable thrusting jets; half of them with 30 degrees angle and the other half with 15 degrees, to fit customers flush pumps and hose dimensions. There is also a front jet, which can be plugged when not used. GOBLIN™ L is made of quality stainless steel. Can be supplied with replaceable wear body.












# GOBLIN™

## GOBLIN S

2-11355-C01

2-11355-C02




	1/2"	3/4"
	100-300 mm (4"-12")	
	30 l/min (8 US GPM)	
	250 bar / 3500 PSI	
	✓	
	4 x M6	
	1 x M6	
	2	
	170 x 90 mm	
	0,8 kg	
	Lev. med släde / Supplied w/ sled(s)	












## GOBLIN L

2-11650-C01

2-11650-C02

2-11650-C03



	3/4"	1"	1 1/4"
	150-800 mm (6"-32")		
	150 l/min (40 US GPM)		
	250 bar (3500 PSI)		
	✓		
	10 x 1/8"		
	1 x 1/8"		
	2		
	205 x 98	205 x 98 mm	190 x 98 mm
	5,5 kg	5,5 kg	5,3 kg
	Kan levereras med slitkropp / Wearbody available.		
	Adapter	Adapter	-

 Anslutning  
Connection


 Vattenflöde vid 100 bar  
Water flow at 1450 PSI

 För recyclers  
For recyclers

 Främre dysor  
Front jets

 Längd x Diameter  
Length x Diameter

 Rördimension  
Pipe dimension

 Max arbetstryck  
Max. working pressure

 Bakre dysor  
Rear jets

 Antal slädar  
No. of sleds

 Vikt  
Weight