



PUMPADUKT S

Sug- och tömningsslang för petroleumprodukter med en aromathalt upp till 50%. Används även som leveransslang för olja och bensin.

Egenskaper

Robust slang med hög flexibilitet

Teknisk beskrivning

- Innertub: Olje- och bensinbeständigt NBR (svart, slät)
- Armering: Syntetisk textil med stålspiral
- Yttergummi: Olje- och väderbeständigt NBR/PVC (svart, korrugerad, vävmönstrat)
- Temperaturområde: -40°C till +100°C
- Elektriska egenskaper: Ledande innertub och yttergummi



PUMPADUKT S

Suction and discharge of petroleum products with aromatic content up to 50%. Loading and unloading of boats and road or rail tankers. Fixed installations in various industries.

Advantages










Highly robust and flexible

Technical description


- Inner tube: Oil- and petrol resistant NBR (black, smooth)
- Reinforcement: Synthetic textile, braided with embedded steel helix
- Cover: Oil- and weather resistant CR (black, fabric impression)
- Temperature range: -40°C to +100°C
- Electrical properties: Conductive tube and cover

PUMPADUKT S



	8-32599	8-32607	8-32615	8-32631
	50 mm (2")	63 mm (2½")	75 mm (3")	100 mm (4")
	66 mm	79 mm	91 mm	116 mm
	16 bar			
	0,9 bar			
	-40°C – +100°C			
	2,29 kg/m	2,93 kg/m	3,65 kg/m	5,85 kg/m
	275 mm	300 mm	350 mm	450 mm
	20 / 40 m			
	TB12050			

 Innerdiameter
Inner diameter

 Max arbetstryck
Max. working pressure

 Temperaturområde
Temperature working area

 Böjningsradie
Bending radius

 Övrig information
Other information

 Ytterdiameter
Outer diameter

 Max vakuum
Max vacuum

 Vikt
Weight

 Leveranslängd
Delivery length