



## TRELLVAC HANDLER HD

Arbets slang för hantering av hårt slitande material. Slangen används när slitstyrkan är av högsta prioritet som t.ex. på saneringssugbilar.

### Egenskaper

Lätt och flexibel konstruktion, med mycket god slitstyrka och väderbeständighet.

### Teknisk beskrivning

- Innertub: Slitbeständigt NR, svart
- Armering: Syntetisk textil med stålspiral
- Yttergummi: Slitstarkt och väderbeständigt SBR (svart, korrugerad)
- Temperaturområde: -30°C till +90°C
- Elektriska egenskaper: Ledande. Spiralen kan användas som ledare vid kopplingarna. Slangen är även försedd med avledarwire.



## TRELLVAC HANDLER HD

Working hose for vacuum cleaning trucks. Extraction and transport of highly abrasive materials.

### Advantages

Light and flexible with high wear and weather resistance.

### Technical description


- Inner tube: Wear resistant NR (black, smooth)
- Reinforcement: Synthetic textile, woven fabric with embedded steel helix
- Cover: Wear and weather resistant SBR (black, corrugated)
- Temperature range: -30°C to +90°C
- Electrical properties: Conductive tube

# TRELLVAC HANDLER HD



	8-1869170	8-1869180	8-1869190	8-1869200
	102 mm (4")	127 mm (5")	152 mm (6")	204 mm (8")
	114 mm	139 mm	164 mm	217 mm
	5 bar			
	0,9 bar	0,8 bar	0,6 bar	
	-30°C – +90°C			
	3,5 kg/m	4,3 kg/m	5,0 kg/m	7,1 kg/m
	400 mm	500 mm	600 mm	800 mm
	20 / 40 m	20 / 40 m	20 m	12 m
	ID5100			

 Innerdiameter  
Inner diameter

 Max arbetstryck  
Max. working pressure

 Temperaturområde  
Temperature working area

 Böjningsradie  
Bending radius

 Övrig information  
Other information

 Ytterdiameter  
Outer diameter

 Max vakuum  
Max vacuum

 Vikt  
Weight

 Leveranslängd  
Delivery length