



TRELLVAC HANDLER MD

Arbets slang för saneringsugbilar. TRELLVAC Handler MD är en arbets slang för lätta material där god rörlighet eftersträvas.

Egenskaper

Lätt och flexibel konstruktion med mycket god slitstyrka.

Teknisk beskrivning

- Innertub: Slitbeständigt NR, svart
- Armering: Syntetisk textil med stålspiral
- Yttergummi: Slitstarkt och väderbeständigt SBR (svart, korrugerad)
- Temperaturområde: -30°C till +90°C
- Elektriska egenskaper: Icke ledande. Spiralen kan anslutas till kopplingarna i bägge ändar om elektrisk ledning önskas.



TRELLVAC HANDLER MD

Medium duty working hose on vacuum cleaning trucks and for use at the work site.

Advantages









Light and flexible with good wear resistance

Technical description










- Inner tube: Wear resistant NR (black, smooth)
- Reinforcement: Synthetic textile, woven fabric with embedded steel helix
- Cover: Wear and weather resistant SBR (black, corrugated)
- Temperature range: -30°C to +90°C
- Electrical properties: Non-conductive tube

TRELLVAC HANDLER MD



	8-1776690	8-1776700	8-1776705	8-1776710
	76 mm (3")	102 mm (4")	127 mm (5")	152 mm (6")
	91 mm	118 mm	144 mm	167 mm
	5 bar			
	0,9 bar			
	-30°C – +90°C			
	2,0 kg/m	2,9 kg/m	3,9 kg/m	4,5 kg/m
	350 mm	400 mm	500 mm	600 mm
	12 m			
	ID4500			

8-1776720

	204 mm (8")
	224 mm
	3 bar
	0,9 bar
	-30°C – +90°C
	7,0 kg/m
	800 mm
	12 m
	ID4500

 Innerdiameter
Inner diameter

 Max arbetstryck
Max. working pressure

 Temperaturområde
Temperature working area

 Böjningsradie
Bending radius

 Övrig information
Other information

 Ytterdiameter
Outer diameter

 Max vakuum
Max vacuum

 Vikt
Weight

 Leveranslängd
Delivery length